M SERIES

Up to Pace...

In today's fast paced world, time is a luxury that many cannot afford to waste. Factors such as convenience and the need for fast, accurate service are now more important than ever. That's why we created the M-Series. The Lion M-Series safe is made to suit businesses that cater to the fast paced consumer. Businesses like fastfood outlets, service stations and clubs where cash transactions take place.

MT SERIES



M SERIES



Quality tested & certified by SIRIM and FRIM

TECHNICAL DIMENSION & DETAILS 650mm 750 mm

				D	IME	NSI	ION	OF I	BOI	YC						
		M1		M2			Мз			M4			M5			
		w	D	H	W	D	H	W	D	Н	W	D	Н	W	D	H
EXTERNAL	mm	550	600	650	650	700	800	650	700	1000	650	700	1550	750	850	1550
INTERNAL	mm	395	410	500	495	510	650	495	510	850	495	510	1400	595	660	1400
CAPACITY	litres		81			164			214			353			550	
NET WEIGHT	kgs		324			490			565			845			1038	
SHIPPING																
DIMENSION	mm	670	750	900	770	850	1050	770	850	1250	770	850	1800	870	1000	1800
SIIII I ING																
VOLUME	cu.m		0.45			0.69			0.82	2		1.18	В		1.57	7
GROSS WEIGHT	kgs		380			550			647	7		953	3		114	2
BOLTS	Ø32															
TOP-EDGE-																
воттом	No.		1-3-1			1-3-1			1-5-	1		1-5-	1		1-5-	1
		PF	ROVID	ED	PR	OVID	ED	P	ROVII	DED	Р	ROVI	DED	PI	ROVII	DED



OTHER DETAILS										
Unit with Drawer Trap	Net Weight KGS	Dimension (External) W D H		Shipping Volume	Gross Weight	Bottom Drawer				
MT1	412	550 600 808	670 750 1060	0.54	462	Not Provided				
MT2	618	650 700 958	770 850 1210	0.80	683	Provided				

SPECIAL FEATURES

- MegaMix 1: A newly developed burglar-and-fire resistant agglomerate of high density and strength,
- impervious to the blowtorch as well as providing effective resistant to hand and mechanical tools.

 Body: Of monolithic construction, the overall thickness is 75mm, incorporating MegaMix 1 Material.

 Door: The protective thickness is 55mm embodying MegaMix 1 Material reinforced with steel and a
- drill-resisting plate protecting the lock area.
- Additional protection against point-attack is given to vital parts of the boltwork by means of drill-resisting deflectors.
- The Standard locking is one Cawi (Germany) keylock, plus a S & G 3-wheel combination lock. Boltwork: Improved boltworks with top and bottom bolts and fixed rebate at the rear. Each bolt is 32mm in diameter.
- A passive relocking device, independent of the locks, will automatically block the moving boltwork in the
- event of a determined attack against the door.

 Base Fixing: Available as an optional extra.

Optional inner compartment(combi safe)



Optional digital lock

