



DESIGNED TO RESIST
AGAINST **HIGH SPEED**
DRILLS AND FORCE



2" STRONGROOM DOOR

BURGLARY RESISTANT PROTECTION



KEY FEATURES

- Solid door slab with a protective thickness of 50mm (2") forms the basis of the door, which has an overall thickness of 165mm. Filled with special formulated Chubb Safes F80 barrier material reinforced with steel fibres provides resistant to high speed drilling, oxy-acetylene cuttings and jack attacks
- Secured by 7 active front bolts, 2 active top bolts, 2 active bottom bolts and 7 passive back bolts. Each bolt has a diameter of 32mm.
- Fire Resistance tested in according to BS476 Part 22:1987 Fire Test on Building Material and Structure for a 120 minutes fire resistant rating.
- Secured by a 3-wheel Keyless Combination Lock and a 8-lever double bitted Key Lock as standard. Both locks operated independently.
- The Keyless Combination Lock is protected by Glass Relockers. Any forced attempt to dislodge the locks would activate relocker and restricts the movement of the internal boltwork system.
- Relocker is further protected by drill resistant hard plates.
- The door comes standard with a painted grey primer based finish.

2" STRONGROOM DOOR

PRODUCT SPECIFICATIONS

Model	External Dimensions (mm)	Clear Opening (mm)	Wall Opening (mm)	Wall Thickness (mm)	Approx. Net Weight (kg)
2"	2110(H) x 1273(W)	1920(H) x 814(W)	2060(H) x 1070(W)	200 (inclusive of Plastering)	640 (Door) and 20 (Gate)

STANDARD LOCKS



KEYLESS COMBINATION LOCK

Secured by a 3-wheel Keyless Combination Lock capable of 1,000,000 changes of code. The operation of this lock is simple. The code can be changed easily and security can be maintained over the safe whenever there is a change of staff.



KEYLOCK

The door is secured by a 8-lever double bitted key lock from Germany

"WRAP AROUND WALL" FRAME



Door frame is fabricated from steel sections, bent to form a single structure. Vestibule side frames at full height of the door are attached to the frame and grip the inside of wall.

This design provides stronger resistance against attacks to the door.

WHEN ORDERING, PLEASE STATE:

- Thickness of RC Wall
- Hung of door required
- If to be installed in multi-storey building, state floor level
- Path of access to where door is to be installed.

NOTE

Chubb safes Doors are designed primarily against physical attack, but for recommended storage of paper documents and computer media, ask for details of Chubb safes Fire Resistant Protection Cabinet or Chubb safes Data Cabinets.

OPTIONS



LOCKS:

- Electronic Lock
- A Dial Check Lock can be fitted as an option to the combination lock.
- Two or three movement Time Lock may be fitted as an additional requirement



EMERGENCY VENTILATOR

Emergency ventilator can be fitted as an option.



DAY GATE

An Optional Day Gate can be fitted to the door for ventilation during the day or as control when the door is open. The Day Gate is secured by two high security 5-lever Mortice Deadlocks.

Authorised dealer